

# LED BALLS

RGB

**RGB:** Management through:

- DMX 512 controllers.
- Wireless IR & RF control units.
- DALI Protocol devices.
- Ideal for ambient lighting
- Impressive decorative elements



Code*	No.LED	Colour	Watt	Diameter/ Height	Voltage
-------	--------	--------	------	---------------------	---------

**WALL MOUNTED**


<b>BAL.101</b> /CC	64	RGB	5W	150mm (Φ)	24VDC
<b>BAL.102</b> /CC	90	RGB	7W	250mm (Φ)	24VDC
<b>BAL.103</b> /CC	148	RGB	9W	300mm (Φ)	24VDC

**PENDANT**

<b>BAL.001</b> /CC	64	RGB	5W	150mm (Φ)	24VDC
<b>BAL.002</b> /CC	90	RGB	7W	250mm (Φ)	24VDC
<b>BAL.003</b> /CC	148	RGB	9W	300mm (Φ)	24VDC

**With STAND**

<b>BAL.201</b> /CC	64	RGB	5W	600mm (h)	24VDC
<b>BAL.202</b> /CC	90	RGB	7W	600mm (h)	24VDC
<b>BAL.203</b> /CC	148	RGB	9W	600mm (h)	24VDC
<b>BAL.211</b> /CC	64	RGB	5W	1140mm (h)	24VDC
<b>BAL.212</b> /CC	90	RGB	7W	1140mm (h)	24VDC
<b>BAL.213</b> /CC	148	RGB	9W	1140mm (h)	24VDC
<b>BAL.221</b> /CC	64	RGB	5W	1680mm (h)	24VDC
<b>BAL.222</b> /CC	90	RGB	7W	1680mm (h)	24VDC
<b>BAL.223</b> /CC	148	RGB	9W	1680mm (h)	24VDC



\*CC=Common Cathode

**RGB:** Management through:

- DMX 512 controllers.
- Wireless IR & RF control units.
- DALI Protocol devices.
- Ideal to create video wall or advertising board that projects words and geometric elements
- Attracts attention from a distance
- Robust construction



# LED EPIGRAM

RGB



Code*	No.LED	Colour	Watt	Diameter	Voltage
-------	--------	--------	------	----------	---------

<b>LED.035</b> /CC	18 (6per colour)	RGB	1.8W	40mm	24VDC
--------------------	------------------	-----	------	------	-------

\*CC=Common Cathode

