


- ARTTUBE linear luminaire is available with 15° or 35° degrees.
- L90/B10 50000h
- 3 SDCM
- IP40

Lighting management options:
On-Off/DALI/0..10V/1..10V/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth



Available upon request:

- ✓ Custom dimensions
- ✓ Custom luminaire colours
- ✓ Emergency version




LIGHTSOURCE BY
NICHIA


IP40

Model	Luminaire Colour	CCT	CRI	Type	Watt / Length	Voltage
ARTTUBE Surface <i>(ARTTUBE SF)</i>	Anodized (AN)	2000K (20N)	≥ 80 (80)	15° (15)	7W / 35cm (07W035)	24VDC (24)
		2500K (25N)		35° (35)	12.2W / 60cm (12W060)	
		2700K (27N)		Milky (ML)	17.5W / 85cm (17W085)	
ARTTUBE Pendant <i>(ARTTUBE PD)</i>		3000K (30N)		Transparent (TR)	21W / 102cm (21W102)	
		4000K (40N)		24.5W / 119cm (24W119)		
		4000K (40N)		31.5W / 152cm (31W152)		
		5700K (57N)		42W / 202cm (42W202)		

Ordering Code Example: ARTTUBE SF-AN-30N-80-ML-24W119-24



Surface with bracket



Pendant

