

# DALI to CONSTANT VOLTAGE Drivers - Converters



- Extended support for DALI protocol, IEC62386, IEC60929, the definition of DALI protocol.
- Automatic addressing and address extensions.
- Supports push dim operation.

| Code        | Supply Voltage | PWM Output Voltage                                      | Output Channels | Channel Power           | Address Setting | Push Dim  |
|-------------|----------------|---|-----------------|-------------------------|-----------------|-----------|
| DEM.190     | 12V-36VDC      | Depending on the power supply<br>0...12VDC or 0...36VDC | 4               | 4x(96-288)W             | Auto            | Supported |
| DEM.160 /CA | 12V-24VDC      | Depending on the power supply<br>0...12VDC or 0...24VDC | 3               | 3x(60-120)W             | Auto            | Supported |
| DEM.161     | 12V-24VDC      | Depending on the power supply<br>0...12VDC or 0...24VDC | 1               | 60W (12V) or 120W (24V) | Auto            | Supported |
| DEM.165     | 100V-240VAC    | 0...12VDC   | 1               | 135W                    | Auto            | Supported |
| DEM.167     | 100V-240VAC    | 0...24VDC   | 1               | 150W                    | Auto            | Supported |
| DEM.184     | 175V-264VAC    | 0...24VDC   | 1               | 75W                     | Auto            | Supported |
| PCK.371     | 100V-240VAC    | 0...24VDC   | 1               | 36W                     | Auto            | Supported |

