



- ROLL outdoor luminaire suitable for surface installation.
- It has minimal aesthetic with no visible screws.
- It is available in black or white colour as standard but RAL colours are also available upon request.
- Marine treatment is also available upon request ensuring higher resistance to weather, UV, water and mould growth.
- Body material: aluminium.
- The luminaire can be customized with the use of softening lens, line spread lens and honeycomb supplied as extra.
- UGR < 19 (6°, 15°, 30°, 46°)
- Power supply cable required: 3x0,75mm² with maximum external diameter 7mm.
- 3 SDCM
- L90/B10 50000h
- Ingress Protection: IP65



IP65

Model	LED Power	CCT	CRI80, CRI90 LED Source	Beam Angle	Shape	Type	Colour*	Dimming Option	Accessories
			80 (80) 90 (90)						
ROLL (ROLL)	6.5W (07)	2700K (27C)	713lm 570lm	15° (15)	Round (RD)	Fixed (FX)	Black (BL)	Without Driver (00)	COVER Standard (0x) Honeycomb (1x) Softening lens (2x) Line spread lens (3x) ↓ (XX) ↑ EXTRAS No Extras (0)
		3000K (30C)	713lm 615lm	30° (30)				230V Phase Cut (PC)	
		4000K (40C)	765lm 660lm	46° (46)				230V Non Dimmable (230ND)	
		5000K (50C)	765lm 713lm					24VDC PWM Dimmable (24DM)	
		6500K (65C)	765lm -					48VDC PWM Dimmable (48DM)	
	4.1W (04)	2700K (27C)	440lm 355lm	6° (06)	Without Driver (00)				
		3000K (30C)	440lm 380lm			230V Non Dimmable (230ND)			
		4000K (40C)	475lm 410lm			24VDC PWM Dimmable (24DM)			
		5000K (50C)	410lm 440lm			48VDC PWM Dimmable (48DM)			

* Available in RAL colours upon request.



ACR.053
Honeycomb
(as extra)



ACR.050
Softening lens
(as extra)



ACR.051
Line spread lens
(as extra)

Ordering Code Example: ROLL 07-30C-90-46-RD-FX-BL-230ND-10

