

# STANDARD SERIES 60LED/m

## Monochromatic

Lighting management options:  
On-Off/DALI/0..10V/1..10V/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth



Monochromatic 12VDC

Code	No.LED/m	Watt/m	Reel(m)	CCT/Colour*	Luminus FLUX (lm/m)	Voltage	Beam Angle	✂ *(mm)	IP Rate**
<i>IP20</i>									
<b>TIV.249</b>	60	4.8W	5	2200-2400K	240	12VDC	120°	50	IP20
<b>TIV.206</b>	60	4.8W	5	2600-2900K	260	12VDC	120°	50	IP20
<b>TIV.143</b>	60	4.8W	5	2900-3300K	280	12VDC	120°	50	IP20
<b>TIV.214</b>	60	4.8W	5	3900-4300K	310	12VDC	120°	50	IP20
<b>TIV.142</b>	60	4.8W	5	5700-6300K	350	12VDC	120°	50	IP20
<b>TIV.141</b>	60	4.8W	5	RED	-	12VDC	120°	50	IP20
<b>TIV.140</b>	60	4.8W	5	GREEN	-	12VDC	120°	50	IP20
<b>TIV.139</b>	60	4.8W	5	BLUE	-	12VDC	120°	50	IP20
<b>TIV.144</b>	60	4.8W	5	AMBER	-	12VDC	120°	50	IP20
<i>IP65</i>									
<b>TIV.250</b>	60	4.8W	5	2200-2400K	240	12VDC	120°	50	IP65
<b>TIV.219</b>	60	4.8W	5	2600-2900K	240	12VDC	120°	50	IP65
<b>TIV.162</b>	60	4.8W	5	2900-3300K	260	12VDC	120°	50	IP65
<b>TIV.215</b>	60	4.8W	5	3900-4300K	290	12VDC	120°	50	IP65
<b>TIV.161</b>	60	4.8W	5	5700-6300K	225	12VDC	120°	50	IP65
<b>TIV.158</b>	60	4.8W	5	RED	-	12VDC	120°	50	IP65
<b>TIV.163</b>	60	4.8W	5	BLUE	-	12VDC	120°	50	IP65
<b>TIV.198</b>	60	4.8W	5	AMBER	-	12VDC	120°	50	IP65

\* Available in other colours upon request

\*\* Please confirm the connection points on the modules

