TALUS

Ceiling Surface

- TALUS fixed downlight is available for surface or pendant installation.
- With a consumption of up to 31W is suitable for applications that require high lumen output.
- Available in black or white colour.
- 3 SDCM
- L90/B10 50.000h

LIGHTSOURCE BY bridgelux

Model (LED Power*)	CCT**	CRI80, CRI90 LED Source 80 (80)	90 (90)	Type	Beam Angle	Colour	Dimming Option***	Accessories
TALUS Surface 23.9W (TALUS SF 24) / **TALUS Pendant 23.9W** (TALUS PD 24)	2700K (27B)	3621lm	2987lm	Fixed (FX)	20° (20)	White (WH)	Without Driver (00)	ANTI-GLARE SHIELD: White Matt (1X)
	3000K (30B)	3847lm	3123lm		40° (40)	Black (BL)	Non Dimmable (ND)	Black Matt (2X)
	4000K (40B)	3960lm	3304lm		60° (60)		Analogue (1-10V) (A1)	Gold Matt (3X)
	5700K (57B)	3847lm	-				DMX (DX)	(XX)
TALUS Surface 31.3W (TALUS SF 31) / **TALUS Pendant 31.3W** (TALUS PD 31)	2700K (27B)	4510lm	3721lm				DALI (DL)	
	3000K (30B)	4792lm	3890lm				Push Button (PB)	EXTRAS:
	4000K (40B)	4933lm	4115lm				Phase Cut (PC)	No Extras (X0)
	5700K (57B)	4792lm	-					
Warm Dimmable		CRI95 95 (95)	LED Source 2840lm					
TALUS WD Surface 30.7W (TALUS WD SF 31) / **TALUS WD Pendant 30.7W** (TALUS WD PD 31)	Warm Dimmable 1800K~3000K (WD)							

* In 31W models the driver must be externally installed.
** Models with CCTs of 3500K, 5000K & 6500K are available upon request.
*** DMX drivers for Pendant (24W & 31W) and 31W Surface models must be externally installed.

Ordering Code Example: *TALUS SF31-30B-80-FX-60-BL-DL-20*



Warm dimming 3000K to 1800K



Pendant model



ELECTRON SA, PROFESSIONAL LIGHTING SYSTEMS - 68 Antiohias Str, N.Philadelphia, 14341 Athens, Greece, info@electron.gr, www.electron.gr

ELECTRON