

ELECSYS / ELECSYS QUATRO

Interior Linear 


- Linear LED lighting with transparent or milky cover.
- Monochromatic or RGBin1 (Common Anode).
- L90/B10 50.000h (for monochromatic models)
- IP40

Monochromatic lighting management options:

- DMX 512 controllers & converters 0-10V or 1-10V or simple push buttons.
- Wireless IR & RF control units.
- DALI Protocol devices.

RGBin1 lighting management options:

- 4 channels DMX controller with 24VDC PWM output.



Available upon request:

- ✓ Custom dimensions
- ✓ Custom luminaire colours
- ✓ Emergency version


LIGHTSOURCE BY
NICHIA
for Monochromatic

IP40

Model	Luminaire Colour*	Colour Temperature	CRI	Type	Watt* / Length	Voltage
ELECSYS (ELECSYS)	Anodized (AN)	2000K (20)	≥ 80 (80)	Transparent (TR)	7W / 36.3cm (07W036)	24VDC (24)
	White (WH)	2500K (25)		Milky (ML)	10.5W / 53cm (11W053)	
	Black (BL)	2700K (27)			17.5W / 86.3cm (18W086)	
		3000K (30)			21W / 103cm (21W103)	
		4000K (40)			24.5W / 119.7cm (25W120)	
		5700K (57)			31.5W / 153cm (32W153)	
					42W / 203cm (42W203)	
		TUNABLE WHITE			6.7W / 36.3cm (07W036)	
		Tunable White			10W / 53cm (10W053)	
		2700K-5700K (TW)			15W / 78cm (15W078)	
ELECSYS QUATRO (ELECSYS QUATRO)		RGBWin1	RGBWin1 (RGBW)		20W / 103cm (20W103)	
					25W / 128cm (25W128)	
					30W / 153cm (30W153)	
					40W / 203cm (40W203)	
					7.8W / 31cm (08W031)	
					15.6W / 60cm (16W060)	
					21.4W / 81cm (21W081)	
					33.1W / 124cm (33W124)	
					48.6W / 182cm (49W182)	
					53.5W / 197cm (53W197)	

* Available in other colours or/and power upon request.


Ordering Code Example: ELECSYS-AN-30-80-ML-21W103-24



with Stainless Steel Holder



with Bracket



ELA.008
STAINLESS STEEL HOLDER
(as standard)



ACC.048
BRACKET
(as extra)