

PRIME SERIES 84LED/m 21W/m CRI80+

Prime series is the finest series of LED strips, produced with NICHIA LEDs offered with 3 step MacAdam as standard. The series is offered also at low CCTs: 2000K and 2500K besides the standard CCTs. The series has an excellent lumen efficacy that reaches up to 138lm/W. It can ideally be used with the appropriate aluminium profiles and IP20 version is offered with adhesive 3M tape on the rear side.

Lighting management options:
On-Off/DALI/0..10V/1..10V/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth

L90/B10 50.000h
3 Step MacAdam



L90/B10 50000h	3 Step MacAdam	80+ CRI	up to 138 lm/W	24VDC	5 years Warranty
-------------------	-------------------	------------	-------------------	-------	---------------------

Code	No.LED/m	Watt/m	Reel(m)	CCT / CRI	Luminus FLUX (lm/m)	Voltage	Beam Angle	* (mm)	IP Rate**
<i>IP20</i>									
TIV.329	84	21W	5	2000K / 80+	1912	24VDC	120°	83.33	IP20
TIV.330	84	21W	5	2500K / 80+	2039	24VDC	120°	83.33	IP20
TIV.339	84	21W	5	2700K / 80+	2467	24VDC	120°	83.33	IP20
TIV.343	84	21W	5	3000K / 80+	2550	24VDC	120°	83.33	IP20
TIV.347	84	21W	5	4000K / 80+	2829	24VDC	120°	83.33	IP20
TIV.351	84	21W	5	5700K / 80+	2907	24VDC	120°	83.33	IP20
<i>IP65</i>									
TIV.331	84	21W	5	2000K / 80+	1897	24VDC	120°	83.33	IP65
TIV.332	84	21W	5	2500K / 80+	2003	24VDC	120°	83.33	IP65
TIV.340	84	21W	5	2700K / 80+	2420	24VDC	120°	83.33	IP65
TIV.344	84	21W	5	3000K / 80+	2520	24VDC	120°	83.33	IP65
TIV.348	84	21W	5	4000K / 80+	2805	24VDC	120°	83.33	IP65
TIV.352	84	21W	5	5700K / 80+	2880	24VDC	120°	83.33	IP65

*Please confirm the connection points on the modules.
**Available in IP66 upon request.

