

REFIT MODULE 10 IP44

- LED module ideal for most GU10/MR16 luminaires
- Easy replacement on existing projects
- High efficiency
- Available in four different beam angles
- Available with different dimming options flexible for any project requirement.
- L90/B10 50.000h
- 3SDCM
- IP44 (face only)



Model	LED Power	CCT*	CRI80, CRI90 LED Source	Beam Angle	Colour**	Dimming Option	Extra
REFIT MODULE <i>(REFIT M)</i>	10.3W (10)	2700K (27B)	80 (80) 90 (90)	18° (18)	White (WH)	Without Driver (00)	No Extras (00)
		3000K (30B)	1379lm 1138lm	24° (24)	Black (BL)	Non Dimmable (ND)	Emergency (01)
		4000K (40B)	1435lm 1180lm	38° (38)	Analogue (1-10V) (A1)	DMX (DX)	
			1479lm 1265lm	60° (60)	DALI (DL)	Push Button (PB)	Phase Cut (PC)
						Wireless*** (WL)	

* CCT: 3500K, 5000K, 6500K available upon request.

** Other RAL colours available upon request.

*** The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example: REFIT M10-30B-80-24-WH-ND-00

