

1ch MULTI POWER LED Drivers Constant Current



- Constant Current output selection:
from 350mA up to 500mA (PCK.320), from 200mA up to 350mA (PCK.216).
- Protections: Short circuits, Overheating, Overloads.
- Non-Dimmable

Code	Supply Voltage	Output Current	Output Voltage	Power Output	Typical ripple of max output current	IP Rate
PCK.320	220-240VAC 50/60Hz	350-500mA*	30-210VDC*	73.5-80W*	≤ 3%**	IP20

*Please refer to the matrix below.

**Referred to $V_n = 230\text{ V}$, 100% load

PCK.320							
P out W	V out DC	I out DC	V out max.	ta °C	tc °C	λ max. Power Factor	η max. Efficiency
73.5	30...210	350 mA cost.	250	-25...+50	85	0.95	>93*
75.5	30...210	360 mA cost.					
77.5	30...210	370 mA cost.					
80	30...210	380 mA cost.					
80	30...205	390 mA cost.					
80	30...200	400 mA cost.					
80	30...195	410 mA cost.					
80	30...190	420 mA cost.					
80	30...186	430 mA cost.					
80	30...181	440 mA cost.					
80	30...177	450 mA cost.					
80	30...174	460 mA cost.					
80	30...170	470 mA cost.					
80	30...166	480 mA cost.					
80	30...163	490 mA cost.					
80	30...160	500 mA cost.					

*Referred to $V_n = 230\text{ V}$, 100% load

