



Ceiling Recessed

CRATER

- Dimmable options.
- 2-3 SDCM
- L90/B10 50.000h



LIGHTSOURCE BY
bridgelux.

Model (LED Power)	Colour Temperature*	LED Lumen	Type	CRI	Beam Angle	Colour	Dimming Option	Accessories
CRATER 12.5W (CRATER 13)	(27B1612)	2700K - 1612lm	Adjustable	(80) 80			(00) Without Driver	COVER (0X) Standard ↓ (XX) EXTRAS (X0) No Extras (X1) Emergency Kit
	(30B1713)	3000K - 1713lm					(ND) Non Dimmable	
	(40B1763)	4000K - 1763lm					(A1) Analogue (1-10V)	
	(57B1713)	5700K - 1713lm					(DX) DMX	
CRATER 12.5W (CRATER 13)	(27B1331)	2700K - 1331lm		(90) 90	(16) 16° (40) 40°	(WH) White	(DL) DALI	
	(30B1391)	3000K - 1391lm				(BL) Black	(PB) Push Button	
	(40B1472)	4000K - 1472lm				(PC) Phase Cut		
CRATER 12.5W (CRATER 13)	(27B1180)	2700K - 1180lm		(97) 97			(WL) Wireless **	
	(30B1260)	3000K - 1260lm						

* Models with CCTs of 3500K, 5000K & 6500K are available upon request.

** The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example:

CRATER 13 - 40B1472 - AD - 90 - 16 - WH - DX - 00

