


Box surface series is a complete series of surface mounted luminaires available in 3 different models in terms of consumption, each offered at different beam angles. Ideal for minimal architectural applications with low glare level due to the design of the luminaire.

- Ingress Protection: IP65
- IK Rate: IK06
- Glare Rating: UGR < 15.1 (17°), < 15.7 (21°), < 14 (28°), < 23.5 (32°), < 25.2 (60°), < 20.3 (16°x30°)
- Dimming options: Phase Cut Dimmable, 24VDC or 48VDC PWM Dimmable.
- Weight: 0,37kg

**L90/B10 >50.000h**





IP65

Model	CCT	LED Source	Beam Angle	Colour	Dimming Option
<b>BOX 4.4W Surface</b> (BOX 5SF)	2700K (27C)	410lm	17°	(VN)	230VAC Phase Cut Dimmable* (230D)
	3000K (30C)	440lm	21°	(NR)	24VDC PWM Dimmable (24D)
	4000K (40C)	475lm	28°	(MD)	48VDC PWM Dimmable (48D)
	6500K (65C)	510lm	32°	(WD)	
			60°	(VV)	
			16°x30°	(AS)	

\* By trailing edge dimmers.

Ordering Code Example: BOX 5SF-30C-WD-WH-230D

