

DULIPO I

Interior Ceiling Recessed 

- Dimmable options.
- Recessed luminaire with round mounting trim in cast aluminium.
- Luminaire body in die-casting aluminium.
- Finish: Electrostatic powder coated in black, white, grey colour.



Model (LED Power)	Colour Temperature*	LED Lumen	Type	CRI**	Beam Angle	Colour	Dimming Option	Accessories
DULIPO I 25W (DULIPO I 25)	(303250)	3000K - 3250lm	(AD) Adjustable	(80) 80+	(12) 12°	(WH) White (BL) Black	(00) Without Driver	COVER (0X) Standard ↓ (XX) ↑ EXTRAS (X0) No Extras (X1) Emergency Kit
	(353350)	3500K - 3350lm			(24) 24°		(ND) Non Dimmable	
	(403400)	4000K - 3400lm			(40) 40°		(A1) Analogue (1..10V)	
	(573550)	5700K - 3550lm					(DX) DMX	
							(DL) DALI	
							(PS) Push Switch	
							(PC) Phase Cut	
							(WL) Wireless ***	

* Available in other CCT upon request.

** Available in CRI90+ upon request (CCT: 3000K/3500K/4000K only).

*** The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example:

DULIPO I 25 - 303250 - AD - 80 - 40 - WH - DL - 00

