

DULIPO II

Interior Ceiling Recessed 

- Dimmable options.
- Recessed luminaire with round mounting trim in cast aluminium.
- Luminaire body in die-casting aluminium.
- Finish: Electrostatic powder coated in black, white, grey colour.



Model (LED Power)	Colour Temperature*	LED Lumen	Type	CRI**	Beam Angle	Colour	Dimming Option	Accessories
DULIPO II 2x25W (DULIPO II 2x25)	(306500)	3000K - 6500lm	Adjustable (AD)	(80) 80+	(12) 12°	(WH) White (BL) Black	(00) Without Driver	COVER (0X) Standard ↓ (XX) ↑ EXTRAS (X0) No Extras (X1) Emergency Kit
	(356700)	3500K - 6700lm			(24) 24°		(DX) DMX	
	(406800)	4000K - 6800lm			(40) 40°		(DL) DALI	
	(577100)	5700K - 7100lm					(PS) Push Switch	
							(PC) Phase Cut	
			(WL) Wireless ***					

* Available in other CCT upon request.

** Available in CRI90+ upon request (CCT: 3000K/3500K/4000K only).

*** The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example:

DULIPO II 2x25 - 306500 - AD - 80 - 40 - WH - DL - 00

