

- Gretto is an outdoor luminaire available in trimless round version.
- Body material: aluminium
- Trimless box: Aluminium dark grey colour or Stainless Steel 316 (ordered as extra).
- The luminaire can be customized with the use of softening lens, line spread lens and honeycomb supplied as extra.
- Safety glass: 6mm
- Power cable HO5RN-F 2x0.75mm² L= 1m
- Cable outer diameter: 6.5mm
- Cable gland: IP67
- Optics available: lenses
- Static load resistance: 2000 kgs
- UGR<19 (6°, 15°, 30°, 46°)
- L90/B10 50000h
- Ingress Protection: IP67
- IK Rate: IK07



Model	LED Power	CCT	CRI80 LED Source	CRI90 LED Source	Beam Angle	Type	Dimming Option	Accessories
			80 (80)	90 (90)				
GRETTO Trimless (GRETTO TR)	6.5W (7)	2700K (27C)	713lm	570lm	15° (15)	Fixed (FX)	Without Driver (00)	COVER Standard (0X) Honeycomb (1X) Softening lens (2X) Line spread lens (3X) ↓ (XX)
		3000K (30C)	713lm	615lm	30° (30)		24VDC PWM Dimmable (24DM)	
		4000K (40C)	765lm	660lm	46° (46)		48VDC PWM Dimmable (48DM)	
		5000K (50C)	765lm	713lm				
		6500K (65C)	765lm	-				
	4.1W (4)	2700K (27C)	440lm	355lm	6° (06)		Without Driver (00)	
		3000K (30C)	440lm	380lm			24VDC PWM Dimmable (24DM)	
		4000K (40C)	475lm	410lm			48VDC PWM Dimmable (48DM)	
		5000K (50C)	410lm	440lm				
							EXTRAS No Extras (1/0) Emergency Kit (1/1)	

* With external IP68 casing box Dali, Phase cut, 1-10V dimming also possible.

Ordering Code Example: GRETTO TR7-30C-90-46-FX-00-10

