JUPITER

- JUPITER is a fixed downlight available with clear or frosted glass.
- Luminaire: Die cast aluminium.
- 3 SDCM
- L90/B10 50000h
- IP65 (face only)

Round

Nickel Satin Diffused glass | Nickel Satin Clear glass | White Diffused glass | White Clear glass



Square (upon request)

Nickel Satin Diffused glass | Nickel Satin Clear glass | White Diffused glass | White Clear glass

ELECTRON SA, PROFESSIONAL LIGHTING SYSTEMS - 68 Antiohias Str, N.Philadelphia, 14341 Athens, Greece, info@electron.gr, www.electron.gr

LIGHTSOURCE BY bridgelux

IP65
Face only

Model	Power	CCT	CRI80, CRI90 LED Source 80 (80)	90 (90)	Beam Angle	Type	Colour	Dimming Option	Extras
JUPITER (JUPITER)	**6.1W** (6)	2700K (27B)	812lm	677lm	18° (18)	Fixed (FX)	White (WH)	Without Driver (00)	No Extras (0)
		3000K (30B)	845lm	705lm	24° (24)		Nickel Satin (NS)	Non Dimmable (ND)	Emergency Kit (1)
		4000K (40B)	879lm	733lm	32° (32)			Analogue (1..10V) (A1)	
					40° (40)			DMX (DX)	
					Diffused (DF)			DALI (DL)	
	10.3W (10)	2700K (27B)	1379lm	1138lm				Push Switch (PS)	
		3000K (30B)	1435lm	1180lm				Phase Cut (PC)	
		4000K (40B)	1479lm	1265lm				Wireless ** (WL)	
	Warm Dimmable			95 (95)				Analogue (1..10V) (A1)	
	6.1W (6)	Warm Dimmable (WD) 1800K–3000K	518lm					DALI (DL)	
								Phase Cut (PC)	
								Wireless * (WL)	

* CCT: 3500K, 5000K, 6500K available upon request.
** The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example: *JUPITER 10-30B-80-32-FX-WH-ND-0*

Warm dimming 3000K to 1800K (6W)



18° LOR 0.46



24° LOR 0.45



32° LOR 0.42



40° LOR 0.39



Diffused° LOR 0.44