

- Merlyn series consists of adjustable downlights in round or square form.
- Available in 18 / 25 / 32 Watt.
- Available with honeycomb, line spread and softening lens as extra.
- 3 SDCM
- L90/B10 50000h
- UGR<10



LIGHTSOURCE BY  
**LUMINUS**  
(for 18W & 25W)

LIGHTSOURCE BY  
**bridgelux**  
(for 32W)

Model	LED Power*	CCT	LED Source	Type	CRI	Beam Angle	Colour	Dimming Option	Accessories
CRI95									
<b>MERLYN XL Round</b> <i>(MERLYN XLR)</i>	<b>18W</b> (18)	2700K (27L)	2000lm	Adjustable (AD)	95 (95)	24° (24)	White (WH)	Without Driver (00) Non-Dimmable (ND) Analogue (1-10V) (A1) DMX (DX) DALI (DL) Wireless** (WL)	<b>COVER</b> Standard (0:) Honeycomb (1:) Line spread lens (2:) Softening lens (3:) (XX)
		3000K (30L)	2115lm			38° (38)	Black (BL)		
		3500K (35L)	2177lm						
		4000K (40L)	2250lm						
		5000K (50L)	2313lm						
<b>MERLYN XL Square</b> <i>(MERLYN XLS)</i>	<b>25W</b> (25)	2700K (27L)	2613lm						<b>EXTRAS</b> No Extras (X0) Emergency Kit (X1)
		3000K (30L)	2763lm						
		3500K (35L)	2845lm						
		4000K (40L)	2940m						
		5000K (50L)	3022lm						
<b>32W</b> (32)	CRI80    CRI90				80 (80) 90 (90)				
	2700K (27B)	4485lm	3701lm						
	3000K (30B)	4766lm	3868lm						
	3500K (35B)	4877lm	4009lm						
	4000K (40B)	4906lm	4092lm						
	5000K (50B)	4962lm	4289lm						

\*Lightsource by LUMINUS for 18W & 25W, and by BRIDGELUX for 32W  
\*\* The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example: MERLYN XLR25-40L-AD-95-38-WH-ND-00

