

- Nordia is an outdoor recessed downlight available either round or square.
- It has minimal aesthetic.
- Body material: aluminium.
- Trim material: Either aluminium electrostatically painted (white, black or other RAL finishes on request) or stainless steel AISI 316.
- Power cable HO5RN-F 2x0.75mm² L= 1m
- Cable outer diameter: 6.5mm
- Cable gland: IP67
- Safety Glass: 6mm
- Optics available: lenses
- Ingress Protection: IP67
- IK Rate: IK07



Model	Power	CCT	CRI80 LED Source	Beam Angle	Shape	Type	Colour*	Dimming Option**	Extras
			80 (80)						
NORDIA DIFFUSED <i>(NORDIA DF)</i>	2.1W (2)	2700K (27B) 3000K (30B) 4000K (40B)	261lm 271lm 286lm	Diffused (DF)	Round (RD) Square (SQ)	Fixed (FX)	White (WH) Black (BL) Stainless (SS) Steel	Without Driver (00) 2448VDC Non Dimmable (2448ND) 24VDC PWM Dimmable (24DM) 48VDC PWM Dimmable (48DM) 230V Non Dimmable (230ND)	No Extras (0) Emergency Kit (1)

* Other RAL finishes available on request.
** With external IP68 casing box Dali, Phase cut, 1-10V dimming also possible.

Ordering Code Example: *NORDIA DF2-30B-80-DF-SQ-FX-SS-00-0*

