

STANDARD SERIES 108, 84, 60, 48 LED/m

RGBW-RGBWW-RGBCW 4in1 chip

Lighting management options:
DALI/DMX512/PHASE CUT/IR/RF/Bluetooth



Adjustable CCT
RGBW, RGBWW, RGBCW

24VDC

Code	No.LED/m	Watt/m	Reel(m)	CCT		Voltage	Beam Angle	✂ *(mm)	IP Rate
<i>IP20</i>									
TIV.240 /CA	84	27W	5	RGBWW 4in1 (2700K)	Adjustable	24VDC	120°	71.5	IP20
TIV.241 /CA	60	19.5W	5	RGBWW 4in1 (2700K)	Adjustable	24VDC	120°	100	IP20
TIV.243 /CA	84	27W	5	RGBCW 4in1 (6000K)	Adjustable	24VDC	120°	71.5	IP20
TIV.244 /CA	60	19.5W	5	RGBCW 4in1 (6000K)	Adjustable	24VDC	120°	100	IP20
TIV.534 /CA	108	15W	5	RGBW 4in1 (2700K)	Adjustable	24VDC	120°	50.5	IP20
<i>IP65</i>									
TIV.242 /CA	48	15.4W	5	RGBWW 4in1 (2700K)	Adjustable	24VDC	120°	125	IP65
TIV.245 /CA	48	15.4W	5	RGBCW 4in1 (6000K)	Adjustable	24VDC	120°	125	IP65
TIV.533 /CA	108	15W	5	RGBW 4in1 (2700K)	Adjustable	24VDC	120°	50.5	IP65

* Please confirm the connection points on the modules.

