

ZERO ST

Exterior Inground, Surface, Wall, Bollard 

ZERO ST is an inground stainless steel small scale luminaire.

- Housing: stainless steel 316
- Front cover: stainless steel 316
- Glass : Tempered glass T=4mm
- Mounting box: aluminum
- Cable gland: PG7 cooper with nickel coated.
- Power cable: H05RN-F 2x0.75mm² L= 1.5m
- IK Rate: 06
- Ingress Protection: IP67
- Maximum load 320kgs


Lighting management options:

On-Off/DALI(0..10V/1..10V/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth



CREE LEDs

IP67

Colour Model / Temperature	No.LED	Watt	Lumen	Dimensions	Diameter	Max. Kg 	Voltage	Beam Angle*	IP Rate	
ZERO ST / 2700K	1	3W	100lm	Φ40x67mm	40mm	1000Kg	12VDC	25°	IP67	Dimmable
ZERO ST / 3000K	1	3W	110lm	Φ40x67mm	40mm	1000Kg	12VDC	25°	IP67	Dimmable
ZERO ST / 5600K	1	3W	130lm	Φ40x67mm	40mm	1000Kg	12VDC	25°	IP67	Dimmable

*Available in 10°, 40° & 60° degrees upon request.

