


WIRELESS CONTROL 32LED/m



The Wireless Control strip has individually controllable pixels one by one through standard programs of CDS.304 controller. The cutting section of 1LED and 1 IC ensures higher flexibility of installation. It is offered at 2pcs of 80 LEDs (2x2.5m) RGB. 2x240 pixels / 2x7.5m can be controlled with CDS.304 in parallel signal connection. It can ideally be used with the appropriate aluminium profiles and It is offered with adhesive 3M tape on the rear side (IP20 version).






One by one individually controllable LEDs through standard programs of CDS.304 wireless controller. 94 modes with adjustable speed. 2x240 pixels / 2x7.5m in parallel signal connection



| Code | No.LED/m | Watt/m | Reel(m) | Colour | Voltage | Beam Angle | Pixel Pitch* (mm) | IP Rate |
|-------------|----------|--------|----------|--------|---------|------------|-------------------|---------|
| <i>IP20</i> | | | | | | | | |
| TIV.304 | 32 | 9W | 2 x 2.5m | RGB | 5VDC | 120° | 31.2 | IP20 |
| <i>IP65</i> | | | | | | | | |
| TIV.305 | 32 | 9W | 2 x 2.5m | RGB | 5VDC | 120° | 31.2 | IP65 |

*Please confirm the connection points on the modules.

| Code | Supply Voltage | Nr. of modes/ programmes | Control |
|---------|--------------------------|--------------------------|-------------------------------------------|
| CDS.304 | 12VDC PSU is included | 94 | Stand alone or wireless RF remote control |



ACC.244
Holder supplied as extra