

DENDO is a LED spotlight with manually adjustable beam angle from 55° to 15°.

- Housing material: aluminum
- Power cable: HO5RN-F 2x1.0mm² open wires. L = 1 meter for 12VDC version. HO5RN-F 3x1.0mm² open wires. L = 1 meter for 230VAC version.
- Consumption: 12 Watt
- Outdoor installation: IP66
- Available accessories: Plastic spike, Belt accessory.



Selectable beam angle (From 15° to 55°)



IP66

Model	CCT	Luminaire Lumen	CRI	Beam Angle	Luminaire Colour	Voltage	Accessories
DENDO 12W <i>(DENDO 12)</i>	2700K (27C)	max 55° / 390lm min 15° / 170lm	>80 (80)	Adjustable (AD) 15° (min)-55° (max)	Black (BL)	12VDC Dimmable (20-100%) (12) 230VAC Non-Dimmable (230)	No Accessory (N)
	3000K (30C)	max 55° / 400lm min 15° / 180lm			White (WH)		Spike (S)
	4000K (40C)	max 55° / 410lm min 15° / 190lm					Belt (B)
	5600K (56C)	max 55° / 420lm min 15° / 200lm					

Ordering Code Example:
DENDO 12-40C-80-AD-BL-230-S

