

- ZETA downlight.
- High efficiency deep reflector with clear cover glass.

BRIDGELUX

- 3 SDCM
- L90/B10 50.000h

CREE (RGBW)

- White CCT at 4000K. (Other CCTs are available upon request)
- L80/B10 50.000h



Model	Power	CCT*	LED Source			Type	Beam Angle		Colour	Dimming Option	Accessories	
			CR180	CR190	CR197		CR1	CR2				
ZETA (ZETA)	12.3W (12)	2700K (27B)	1662lm	1372lm	1216lm	Fixed (FX)	80 (80)	14° (14)	White (WH) Black (BL)	Without Driver (00) Non Dimmable (ND) Analogue (1-10V) (A1) DMX (DX) DALI (DL) Push Button (PB) Phase Cut (PC) Wireless*** (WL)	COVER Standard (0/1) Honeycomb (1/1) ↓ (X/X) ↑ EXTRAS No Extras (0/0) Emergency (1/1)	
		3000K (30B)	1766lm	1434lm	1299lm		90 (90)	25° (25)				
		4000K (40B)	1818lm	1517lm	-		97 (97)	39° (39)				
		5700K (57B)	1766lm	-	-							
		17.5W (18)	2700K (27B)	2482lm	2048lm		1815lm					
			3000K (30B)	2637lm	2140lm		1939lm					
	4000K (40B)		2714lm	2265lm	-							
	31.3W (31)	2700K (27B)	4510lm	3721lm	3298lm							
		3000K (30B)	4792lm	3890lm	3524lm							
		4000K (40B)	4933lm	4115lm	-							
	29.5W (30)	RGBW (RGBW)	2075lm					25° (25)		Without Driver (00) DMX (DX) DALI (DL) Wireless*** (WL)	COVER Standard (0/1) ↓ (X/X) ↑ EXTRAS No Extras (0/0)	
			2695lm					39° (39)				
42.5W (43)			2695lm									

* BRIDGELUX: Models with CCTs of 3500K, 5000K & 6500K are available upon request.

** CREE RGBW: Other colour combinations available upon request.

*** The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Examples: ZETA 31-30B-FX-90-39-BL-ND-00

