

1ch DIMMABLE 1-10V CONSTANT CURRENT or CONSTANT VOLTAGE Universal Drivers



- Overload, Short-circuit protection.
- Overheating protection.
- Supports push dim operation.

Code	Supply Voltage	Output Current	Output Voltage	Power Output	Typical ripple at max output current	IP Rate	Dimming
PCK.098	220-240VAC 50/60Hz	250-900mA*	2-53VDC*	13-32W*	≤ 3%**	IP20	1-10V, PUSH

*Please refer to the matrix below.

**Referred to $V_{in} = 230\text{ V}$, 100% load

P out W	V out DC	I out DC	V out max.	ta °C	tc °C	λ max. Power Factor	η max. Efficiency*
13	15-53	250 mA cost.					
16	15-53	300 mA cost.					
18	15-53	350 mA cost.					
21	15-53	400 mA cost.					
23	5-52	450 mA cost.					
25	2-50	500 mA cost.					
27	2-50	550 mA cost.					
30	2-50	600 mA cost.	59	-25...+45	75	0.95	>0.88
32	2-49	650 mA cost.					
32	2-46	700 mA cost.					
20	2-27	750 mA cost.					
20	2-25	800 mA cost.					
20	2-24	850 mA cost.					
20	2-22	900 mA cost.					
11W at 12VDC		Constant Voltage					
20W at 24VDC		Constant Voltage					

*Referred to $V_{in} = 230\text{ V}$, 100%

