

1ch MULTI POWER

LED Drivers Constant Current

- Constant Current output selection from 60mA up to 360mA.
- Protections: Short circuits, overheating, overloads.
- Non-Dimmable



Code	Supply Voltage	Output Current	Output Voltage	Power Output	Typical ripple at max output current	IP Rate
PCK.215	220-240VAC 50/60Hz	60-360mA*	2-41VDC*	2.5-15W*	≤ 3%**	IP20

*Please refer to the matrix below.
 **Referred to $V_{in} = 230\text{ V}$, 100% load

P out W	V out DC	I out DC	V out max.	ta °C	tc °C	λ max. Power Factor	η max. Efficiency*
2.5	2...41.5	60 mA const.	44	-25...+45	75	0.64C	82
3.5	2...41.5	80 mA const.					
4.1	2...41.5	100 mA const.					
5	2...41.5	120 mA const.					
5.8	2...41.5	140 mA const.					
6.6	2...41.5	160 mA const.					
7.4	2...41.5	180 mA const.					
8.3	2...41.5	200 mA const.					
9.1	2...41.5	220 mA const.					
10	2...41.5	240 mA const.					
10.8	2...41.5	260 mA const.					
11.6	2...41.5	280 mA const.					
12.4	2...41.5	300 mA const.					
13.2	2...41.5	320 mA const.					
14.1	2...41.5	340 mA const.					
15	2...41.5	360 mA const.					

*Referred to $V_{in} = 230\text{ V}$, 100% load

