

1ch MULTI POWER LED Drivers Constant Current



- Constant Current output selection:
from 350mA up to 500mA (PCK.320), from 200mA up to 350mA (PCK.216).
- Protections: Short circuits, Overheating, Overloads.
- Non-Dimmable

Code	Supply Voltage	Output Current	Output Voltage	Power Output	Typical ripple at max output current	IP Rate
PCK.216	220-240VAC 50/60Hz	200-350mA*	30-270VDC*	54-80W*	≤ 3%**	IP20

*Please refer to the matrix below.
**Referred to $V_{in} = 230\text{ V}$, 100% load

PCK.216							
P out W	V out DC	I out DC	V out max.	ta °C	tc °C	λ max. Power Factor	η max. Efficiency*
54	30...270	200 mA cost.	390	-25...+50	85	0.95*	>94**
56.5	30...270	210 mA cost.					
59	30...270	220 mA cost.					
62	30...270	230 mA cost.					
64.5	30...270	240 mA cost.					
67.5	30...270	250 mA cost.					
70	30...270	260 mA cost.					
72.5	30...270	270 mA cost.					
72.5	30...270	280 mA cost.					
78	30...270	290 mA cost.					
80	30...266	300 mA cost.	300				
80	30...258	310 mA cost.					
80	30...250	320 mA cost.					
80	30...242	330 mA cost.					
80	30...235	340 mA cost.					
80	30...228	350 mA cost.					
80	30...228	350 mA cost.					

* Pout > 46W
** Referred to $V_{in} = 230\text{ V}$, 100% load

