

# 1ch MULTI POWER LED Drivers Constant Current



- Constant Current output selection from 300mA up to 1050mA.
- Protections: Short circuits, overheating, overloads.
- Non-Dimmable

Code	Supply Voltage	Output Current	Output Voltage	Power Output	Typical ripple at max output current	IP Rate
PCK.484	220-240VAC 50/60Hz	300-1050mA*	3-44VDC*	13-42W*	≤3%**	IP20

\*Please refer to the matrix below.  
\*\*Referred to  $V_{in} = 230\text{ V}$ , 100% load

P out W	V out DC	I out DC	V out max.	ta °C	tc °C	A max. Power Factor	η max. Efficiency*
13	3...44	300 mA cost.	55	-25...+45	80	0.95	≤0.90
15	3...44	350 mA cost.					
18	3...44	400 mA cost.					
20	3...44	450 mA cost.					
22	3...44	500 mA cost.					
24	3...44	550 mA cost.					
27	3...44	600 mA cost.					
29	3...44	650 mA cost.					
31	3...44	700 mA cost.					
32	3...44	750 mA cost.					
33	3...42	800 mA cost.					
35	3...42	850 mA cost.					
38	3...42	900 mA cost.					
40	3...42	950 mA cost.					
42	3...42	1000 mA cost.					
42	3...40	1050 mA cost.					

\*Referred to  $V_{in} = 230\text{ V}$ , 100% load

