

# 1ch MULTI POWER Const.Current NFC PROGRAMMABLE LED Drivers Constant Current

Constant Current LED Drivers 

- NFC Programmable.
- Current selectable output with 1mA step.
- Protections: Short circuits, overheating, overloads.
- Strain relief set to be ordered separately (216.ACC.408).
- Non-Dimmable.



Code	Supply Voltage	Output Current	Output Voltage	Power Output	Typical ripple at max output current	IP Rate
<b>PCK.553</b>	220-240VAC 50/60Hz	100-700mA*	2.5-46VDC*	0.25-15W*	≤ 3%**	IP20

\*Please refer to the matrix below.  
\*\*Referred to  $V_{in} = 230\text{ V}$ , 100% load

P out W	V out DC	I out DC	V out max.	ta °C	tc °C	λ max. Power Factor	η max. Efficiency*
4.6	2.5-46	100 mA cost.	60	-20...+50	85	0.91	87
9.2	2.5-46	200 mA cost.					
13.8	2.5-46	300 mA cost.					
14.8	2.5-37	400 mA cost.					
15	2.5-30	500 mA cost.					
15	2.5-25	600 mA cost.					
14.7	2.5-21	700 mA cost.					

\*Referred to  $V_{in} = 230\text{ V}$ , 100% load.

