

VELA

Ceiling Recessed 

- Dimmable options.
- 2-3 SDCM
- L90/B10 50.000h



VELA 13



VELA DOUBLE 25

LIGHTSOURCE BY
bridgelux

Model (LED Power)	Colour Temperature*	LED Lumen	Type	CRI	Beam Angle	Colour	Dimming Option	Accessories					
VELA 12.5W (VELA 13)	(27B1612)	2700K - 1612lm	(AD) Adjustable	(80) 80				COVER (0X) Standard ↓ (XX) EXTRAS (X0) No Extras (X1) Emergency Kit					
	(30B1713)	3000K - 1713lm											
	(40B1763)	4000K - 1763lm											
	(57B1713)	5700K - 1713lm											
VELA DOUBLE 25.0W (VELA D25)	(27B3224)	2700K - 3224lm											
	(30B3426)	3000K - 3426lm											
	(40B3526)	4000K - 3526lm											
	(57B3426)	5700K - 3426lm											
VELA 12.5W (VELA 13)	(27B1331)	2700K - 1331lm							(90) 90		(16) 16° (40) 40°	(WH) White (BL) Black	(00) Without Driver (ND) Non Dimmable (A1) Analogue (1-10V) (DX) DMX (DL) DALI (PB) Push Button (PC) Phase Cut (WL) Wireless **
	(30B1391)	3000K - 1391lm											
	(40B1472)	4000K - 1472lm											
VELA DOUBLE 25.0W (VELA D25)	(27B2662)	2700K - 2662lm											
	(30B2782)	3000K - 2782lm											
	(40B2944)	4000K - 2944lm											
VELA 12.5W (VELA 13)	(27B1180)	2700K - 1180lm	(97) 97										
	(30B1260)	3000K - 1260lm											
VELA DOUBLE 25.0W (VELA D25)	(27B2360)	2700K - 2360lm											
	(30B2520)	3000K - 2520lm											

* Models with CCTs of 3500K, 5000K & 6500K are available upon request.
 ** The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example:
 VELA D25 - 40B2944 - AD - 90 - 16 - WH - DL - 00

