




Ceiling Recessed

URANUS / URANUS ADJ

- High efficiency deep reflector with clear cover glass.
- Supplied with non-dimmable drivers as standard.
- Dimmable options.
- Increased efficiency
- 2-3 SDCM
- L90/B10 50.000h



LIGHTSOURCE BY
bridgelux

Model (LED Power)	Colour Temperature*	LED Lumen	Type	CRI	Beam Angle	Colour	Dimming Option	Accessories
URANUS A 12.3W (URANUS A12)	(27B1662) 2700K - 1662lm (30B1766) 3000K - 1766lm (40B1818) 4000K - 1818lm							
URANUS 12.3W (URANUS 12)	(57B1766) 5700K - 1766lm				(80) 80			
URANUS A 17.7W (URANUS A18)	(27B2302) 2700K - 2302lm (30B2445) 3000K - 2445lm							
URANUS 17.7W (URANUS 18)	(40B2305) 4000K - 2305lm (57B2415) 5700K - 2415lm							
URANUS A 12.3W (URANUS A12)	(27B1372) 2700K - 1372lm (30B1434) 3000K - 1434lm		(AD) Adjustable		(16) 16°	(WH) White (BL) Black	(00) Without Driver (ND) Non Dimmable (A1) Analogue (1-10V) (DX) DMX	COVER (0X) Standard (2X) Honeycomb ↓ (XX) EXTRAS (X0) No Extras (X1) Emergency Kit
URANUS 12.3W (URANUS 12)	(40B1517) 4000K - 1517lm		(FX) Fixed		(38) 38°	(GR) Grey	(DL) DALI (PB) Push Button (PC) Phase Cut (WL) Wireless **	
URANUS A 17.7W (URANUS A18)	(27B1971) 2700K - 1971lm (30B1985) 3000K - 1985lm				(90) 90			
URANUS 17.7W (URANUS 18)	(40B1973) 4000K - 1973lm							
URANUS A 12.3W (URANUS A12)	(27B1216) 2700K - 1216lm (30B1299) 3000K - 1299lm				(97) 97			
URANUS 12.3W (URANUS 12)								

* Models with CCTs of 3500K, 5000K & 6500K are available upon request.
 ** The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example:
 URANUS A18 - 40B1973 - AD - 90 - 26 - WH - DL - 00

