

# 1ch DALI LED Driver


Constant Current LED Drivers 

- Constant Current output selection from 350mA up to 700mA.
- DALI
- Dimming range 0.01%-100%
- Suitable for TV studios
- Overload, Short-circuit protection
- Overheating protection



Code	Supply Voltage	Output Current	Output Voltage	Power Output	IP Rate
PCK.384	220-240V 50/60Hz	350-700mA*	10-24V*	8-12W*	IP20

\*Please refer to the matrix below.



P out W	V out DC	I out DC	V out max.	ta °C	tc °C	η max. Efficiency*
8	10-24	350 mA const.	35	-25...+50	85	0.88
10	10-24	400 mA const.				
11	10-24	450 mA const.				
12	10-24	500 mA const.				
12	10-22	550 mA const.				
12	10-20	600 mA const.				
12	10-18.5	650 mA const.				
12	10-17	700 mA const.				


\*Referred to  $V_{in} = 230$  V, 100% load

- Constant Current output selection from 350mA up to 700mA.
- DALI, PUSH DIM.
- Dimming range 0.01%-100%
- Suitable for TV studios.
- Overload, Short-circuit protection.
- Overheating protection.
- 1KHz Min PWM.
- LF Current Ripple (<120Hz) <3%



Code	Supply Voltage	Output Current	Output Voltage	Power Output	IP Rate
PCK.422	100-240V 50/60Hz	350-700mA*	2-21V*	0.7-9.8W*	IP20

\*Please refer to the matrix below.



P out W	V out DC	I out DC	V out max.	ta °C	tc °C	η max. Efficiency*
7.35	2-21	350 mA const.	60	-20...+50	90	0.76
8.4	2-21	400 mA const.				
9.45	2-21	450 mA const.				
10	2-20	500 mA const.				
9.9	2-18	550 mA const.				
9.6	2-16	600 mA const.				
9.75	2-15	650 mA const.				
9.8	2-14	700 mA const.				

\*Referred to  $V_{in} = 230$  V, 100% load