


Box surface series is a complete series of surface mounted luminaires available in 3 different models in terms of consumption, each offered at different beam angles. Ideal for minimal architectural applications with low glare level due to the design of the luminaire.

- Ingress Protection: IP65
- IK Rate: IK06
- Glare Rating: UGR < 12.7 (16°), < 12.5 (20°), < 10.5 (26°), < 20.9 (40°), < 23.1 (60°), < 15.1 (16°x30°)
- Dimming options: Phase Cut Dimmable, Non-Dimmable or 48VDC PWM Dimmable.
- Weight: 1,5kg

L90/B10 >50.000h





IP65

Model	CCT	LED Source	Beam Angle	Colour	Dimming Option
BOX 23.8W Surface (BOX 24SF)	2700K (27C)	2457lm	16° (VN)	Black (BL)	230VAC Non-Dimmable (230ND)
	3000K (30C)	2628lm	20° (NR)	White (WH)	230VAC Phase Cut Dimmable* (230D)
	4000K (40C)	2628lm	26° (MD)		48VDC PWM Dimmable (48D)
	6500K (65C)	2948lm	40° (VD)		
				60° (VV)	
			16°x30° (AS)		

* By trailing edge dimmers.

Ordering Code Example: BOX 24SF-30C-NR-BL-230D

