


Box surface series is a complete series of surface mounted luminaires available in 3 different models in terms of consumption, each offered at different beam angles. Ideal for minimal architectural applications with low glare level due to the design of the luminaire.

- Ingress Protection: IP65
- IK Rate: IK06
- Glare Rating: UGR <13.4 (12°), <11.6 (17°), <12.2 (25°), <19.3 (35°), <22.7 (60°), <16.3 (16°x30°)
- Dimming options: Phase Cuf Dimmable, Non-Dimmable, 24VDC or 48VDC PWM Dimmable.
- Weight: 0,60kg

L90/B10 >50.000h





IP65

Model	CCT	LED Source	Beam Angle	Colour	Dimming Option
BOX 9.2W Surface (BOX 9SF)	2700K (27C)	988lm	12° (VN)	Black (BL)	230VAC Non-Dimmable (230ND)
	3000K (30C)	1056lm	17° (NR)	White (WH)	230VAC Phase Cut Dimmable* (230D)
	4000K (40C)	1056lm	25° (MD)		24VDC PWM Dimmable (24D)
	6500K (65C)	1185lm	35° (VD)		48VDC PWM Dimmable (48D)
				60° (VV)	
			16°x30° (AS)		

* By trailing edge dimmers.

Ordering Code Example: BOX 9SF-30C-NR-BL-230D

