



Box series of outdoor spotlights consists of a complete series of 5 different models in terms of consumption, available with accessories for different installations (plastic spike, concrete base, tree belt or pole base). Ideal for minimal architectural applications with low glare level due to the design of the luminaire and the extra snoot accessory. It is available in black or white colour as standard but custom RAL colours are also available upon request. Marine treatment is also offered upon request ensuring higher resistance to weather, UV, water and mould growth.

- Ingress Protection: IP66
- IK Rate: IK06
- Glare Rating: UGR < 18.6 (3°)
- Dimming options: Phase Cut Dimmable or 24VDC PWM Dimmable.
- Power cable: H05RN-F 3x0.75mm² L=2.0m
- Outer cable diameter: 7mm²
- Weight: 0,50kg

L80/B10 50.000h











Tilt: 120° Rotate:60°







Model	сст	LED Source	Beam Angle	Colour	Dimming Option	Accessories
						cover
BOX 2.5W	2700K (27C)	137lm	3° (VN)	Black (BL)	230VAC Phase Cut Dimmable* (230D)	Standard (0X
Narrow	3000K (30C)	149lm		White (WH)	24VDC PWM Dimmable (24D)	SNOOT Black (1X)
(BOX 3N)	4000K (40C)	170lm		, ,		SNOOT White (2X)
	6500K (65C)	265lm				1
						(XX
						extras •
						No Extras (X0)
						Spike (X1)
						Belt (X2)
						Pole Base** (X3)
						Concrete Base 0x4

* By trailing edge dimmers.

** Pole base supplied black as standard.

Ordering Code Example: BOX 3N-30C-VN-BL-230D-01



Accessories



