

CORNER 45 IP67

- CORNER 45 IP67 is a custom made linear luminaire available in standard or custom lenaths.
- Supplied with single waterproof cable & IP68 connector as standard.
- Possibility for in-out cables & IP68 connectors upon request as extra.
- L90/B10 > 50.000h, 3 Step MacAdam.
- Ingress Protection: IP67

Lighting management options:

On-Off/DALI/0..10V/1..10V/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth

L90/B10 >50.000h for monochromatic models

Available upon request:

- √ Custom dimensions
- √ Custom luminaire colours







Model*	Luminaire Colour	сст	Туре	Watt / Length	Voltage
CORNER 45 IP67	Anodized (AN)	2000K (20)	Clear (CL)	7W / 35cm (07W035)	24VDC (24)
(CORNER 45 67)	Marine Type (MT)	2500K (25)	Opal (OP)	12.2W / 60cm (12W060)	
		2700K (27)		17.5W / 85cm (17W085)	
		3000K (30)		21W / 102cm (21W102)	
		4000K (40)		24.5W / 119cm (24W119)	
		5700K (57)		31.5W / 152cm (31W152)	
		1		42W / 202cm (42W202)	

* IP67: Short term immersion protection

Ordering Code Example: CORNER 45 67-AN-30-OP-31W152-24







One outdoor cable and IP68 connector (as standard)

PU (Polyurethane) material:

Tri-component polyurethane, transparent or translucent for homogeneous light dispersion.

Fully compliance with: REACH, RoHS and ELV European Directives. EC - Directives 89/109 Contact with Food.

Resistance to:

Outdoor - Chemicals - Short term water immersion - Hot water. Thermal Shock – Heat - Abrasion Florida test, Arizona test, Xenotest, QUV-A test. ACID Rain test ASTM G87.

TABER test ASTM D1044. CROCKMETER test ASTM D6279

Marine Type features:

Powder Coating:
Ultra-durable powder coating that meets the requirements of GSB Master, Qualicoat Class2, EN12206 (formerly BS6496), EN13438 (formerly BS6497:1984) and AAMA 2604. Exterior Durabiliy:

Meets qualicoat class 2 requirements after 3 years Florida Meets AAMA 2604-13 requirements after 5 years Florida High Resistance to:

Weather, UV, Water and mould growth





In accordance to: