

- DELTA linear surface luminaire ideal for pathways and signage, offers a soft delicate light output.
- Its dot-free light effect makes it suitable for use even on a glossy floor.
- It is available in standard lengths. Custom lengths also available on request.
- Available anodized, White (RAL 9003 mat), Black (RAL 9005 mat) & Brown. Other RAL also available on request.
- Suitable for use only with BASELINE V.
- Monochromatic White LEDs Silicone: 2 Step MacAdam
- L70/B10 > 54000h
- CRI > 90 for 2700/3000/3500/4000K
- Baseline V: IK08 Protection
- Ingress Protection: IP67

Lighting management options:
On-Off/DALI/0...10V/1...10V/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth

Available upon request:

- ✓ Custom dimensions
- ✓ Custom luminaire colours



Suitable only with:
✓ **BASELINE V MILKY LED**

IP67

Model	Luminaire Colour*	Type	CCT	Luminous FLUX	CRI	Watt / Length	Voltage
DELTA IP67 <i>(DELTA 67)</i>	Anodized <i>(AN)</i> White <i>(WH)</i> Black <i>(BL)</i> Brown <i>(BR)</i>	PRO <i>(PR)</i>	2700K <i>(27)</i>	500 lm/m	>90 <i>(90)</i>	5W / 52cm <i>(05W052)</i> 10W / 102cm <i>(10W102)</i> 15W / 152cm <i>(15W152)</i> 20W / 202cm <i>(20W202)</i>	24VDC <i>(24)</i>
			3000K <i>(30)</i>	510 lm/m			
			3500K <i>(35)</i>	515 lm/m			
			4000K <i>(40)</i>	530 lm/m			
			5300K <i>(53)</i>	540 lm/m			
		Standard <i>(ST)</i>	2700K <i>(27)</i>	420 lm/m	>90 <i>(90)</i>		
			3000K <i>(30)</i>	430 lm/m			
			3500K <i>(35)</i>	435 lm/m			
			4000K <i>(40)</i>	450 lm/m			
			5300K <i>(53)</i>	460 lm/m		>80 <i>(80)</i>	

* Available in other colours upon request.

Ordering Code Example: DELTA 67-WH-PR-40-90-20W202-24



