


ELECSIA IP67



- ELECSIA IP67 is a custom made linear luminaire available in standard and custom lengths upon request.
- Ensures uniformity and colour consistency of the lighting output.
- Special design and construction to meet the most demanding lighting designs.
- Multiple mounting options (fixed, surface or pendant).
- Long & Short bracket accessory for wall installation.
- Supplied with input cable & IP68 connector as standard.
- Possibility for in-out cables & IP68 connectors upon request as extra.
- L90/B10 > 50.000h, 3 Step MacAdam (for monochromatic models).
- Ingress Protection: IP67




Lighting management options:
On-Off/DALI/0..10V/1..10V/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth




L90/B10 > 50.000h
for monochromatic models

Available upon request:


- ✓ Custom dimensions
- ✓ Custom luminaire colours




FIXED Installation




SURFACE A Installation




SURFACE B Installation



SURFACE C Installation



WALL BRACKET
(Long/Short) Installation



PENDANT Installation



ELA.008
Antislipper for
vertical installation
(as extra)



Input cable
with IP68 connectors
(as standard)



Input & Output cables
with IP68 connector
(as extra)

PU (Polyurethane) material:

Tri- component polyurethane, transparent or translucent for homogeneous light dispersion.

Fully compliance with: REACH, RoHS and ELV European Directives.

EC – Directives 89/109 Contact with Food.

Resistance to: Outdoor – Chemicals – Short term water immersion – Hot water.

Thermal Shock – Heat - Abrasion

In accordance to: Florida test, Arizona test, Xenotest, QUV-A test, ACID Rain test ASTM G87, TABER test ASTM D1044, CROCKMETER test ASTM D6279

Marine Type features:

Powder Coating:

Ultra-durable powder coating that meets the requirements of GSB Master, Qualicoat Class2, EN12206 (formerly BS6496), EN13438 (formerly BS6497:1984) and AAMA 2604.

Exterior Durability:

Meets qualicoat class 2 requirements after 3 years Florida

Meets AAMA 2604-13 requirements after 5 years Florida

High Resistance to:

Weather, UV, Water and mould growth



WEATHER RESISTANT

Model*	Luminaire Colour**	Colour Temperature	CRI	Watt / Length	Type	Voltage
ELECSIA IP67 FIXED (ELECSIA 67F)	Anodized (AN)	2000K (20)	≥ 80 (80)	10.5W / 53cm (11W053)	Clear (CL) Opal (OP)	24VDC (24)
	Marine Type (MT)	2500K (25)		17.5W / 86.3cm (18W086)		
ELECSIA IP67 SURFACE A (ELECSIA 67SA)		2700K (27)		21W / 103cm (21W103)		
		3000K (30)		24.5W / 119.7cm (25W120)		
		4000K (40)		31.5W / 153cm (32W153)		
		5700K (57)		42W / 203cm (42W203)		
ELECSIA IP67 SURFACE B (ELECSIA 67SB)						
ELECSIA IP67 SURFACE C (ELECSIA 67SC)						
ELECSIA IP67 SHORT BRACKET 6.5cm (ELECSIA 67B1)						
ELECSIA IP67 LONG BRACKET 11.5cm (ELECSIA 67B2)						
ELECSIA IP67 PENDANT (ELECSIA 67P1) H:150cm (ELECSIA 67P2) H:300cm						
RGBWW / RGBCW / RGB						
		Colour		Watt / Length		
		RGBWW (RGBWW)		13.5W / 53cm (14W053)		
		RGBCW (RGBCW)		23.1W / 88.7cm (23W089)		
		84LED/m		27W / 103cm (27W103)		
				32.8W / 124.4cm (33W124)		
				40.5W / 153cm (41W153)		
				54W / 203cm (54W203)		
		RGBWW (RGBWW)		9.7W / 53cm (10W053)		
		RGBCW (RGBCW)		15.6W / 83cm (16W083)		
		60LED/m***		19.5W / 103cm (20W103)		
				23.4W / 123cm (23W123)		
				29.2W / 153cm (29W153)		
				39W / 203cm (39W203)		
		RGB (RGB96)		11.5W / 53cm (12W053)		
		96LED/m		20.1W / 90.5cm (20W091)		
				23W / 103cm (23W103)		
				27.3W / 121.7cm (27W122)		
				34.5W / 153cm (35W153)		
				46W / 203cm (46W203)		
		RGB (RGB60)		7.2W / 53cm (07W053)		
		60LED/m***		11.6W / 83cm (12W083)		
				14.5W / 103cm (15W103)		
				17.4W / 123cm (17W123)		
				21.7W / 153cm (22W153)		
				29W / 203cm (29W203)		
		RGB (RGB30)		3.6W / 53cm (04W053)		
		30LED/m***		5.7W / 83cm (06W083)		
				7.2W / 103cm (07W103)		
				8.6W / 123cm (09W123)		
				10.8W / 153cm (11W153)		
				14.4W / 203cm (14W203)		
						12VDC (12)

* Short term immersion protection.
 ** Available in other colours or/and power upon request.

Ordering Code Example: ELECSIA 67B2-AN-RGB60-22W153-OP-24