


ELECSYS / ELECSYS QUATRO

- Linear LED lighting with transparent or milky cover.
- Monochromatic or RGBin1 (Common Anode).
- L90/B10 50.000h (for monochromatic models)
- IP40



Monochromatic lighting management options:

- DMX 512 controllers & converters 0-10V or 1-10V or simple push buttons.
- Wireless IR & RF control units.
- DALI Protocol devices.

RGBin1 lighting management options:

- 4 channels DMX controller with 24VDC PWM output.



Available upon request:

- ✓ Custom dimensions
- ✓ Custom luminaire colours
- ✓ Emergency version



Model	Luminaire Colour*	Colour Temperature	CRI	Type	Watt* / Length	Voltage
ELECSYS <i>(ELECSYS)</i>	Anodized <i>(AN)</i>	2000K <i>(20)</i>	≥ 80 <i>(80)</i>	Transparent <i>(TR)</i>	7W / 36.3cm <i>(07W036)</i>	24VDC <i>(24)</i>
	White <i>(WH)</i>	2500K <i>(25)</i>		Milky <i>(ML)</i>	10.5W / 53cm <i>(11W053)</i>	
	Black <i>(BL)</i>	2700K <i>(27)</i>		17.5W / 86.3cm <i>(18W086)</i>		
		3000K <i>(30)</i>		21W / 103cm <i>(21W103)</i>		
		4000K <i>(40)</i>		24.5W / 119.7cm <i>(25W120)</i>		
		5700K <i>(57)</i>		31.5W / 153cm <i>(32W153)</i>		
		42W / 203cm <i>(42W203)</i>				
		TUNABLE WHITE				
		Tunable White			6.7W 36.3cm <i>(07W036)</i>	
		2700K-5700K			10W / 53cm <i>(10W053)</i>	
		<i>(TW)</i>			15W / 78cm <i>(15W078)</i>	
					20W / 103cm <i>(20W103)</i>	
					25W / 128cm <i>(25W128)</i>	
					30W / 153cm <i>(30W153)</i>	
					40W / 203cm <i>(40W203)</i>	
ELECSYS QUATRO <i>(ELECSYS QUATRO)</i>		RGBin1			7.8W / 31cm <i>(08W031)</i>	
		RGBin1 <i>(RGBW)</i>			15.6W / 60cm <i>(16W060)</i>	
					21.4W / 81cm <i>(21W081)</i>	
					33.1W / 124cm <i>(33W124)</i>	
					48.6W / 182cm <i>(49W182)</i>	
					53.5W / 197cm <i>(53W197)</i>	

* Available in other colours or/and power upon request.

Ordering Code Example: ELECSYS-AN-30-80-ML-21W103-24



with Stainless Steel Holder



with Bracket

