

# EMERGENCY LIGHT KIT for 230V LED Lamps with Lamp Holder GU10



- Instant emergency operation at mains failure.
- Maintained or not maintained operation (maintained operation suitable with electronic drivers and dimmable electronic drivers).
- Suitable for LED lamps 230V - 0/50Hz.
- High efficiency, minimum heat dispersion and absolute reliability.
- "High temperature" Ni-Cd batteries.
- Charge indicator with LED.
- Protection device against extensive discharge.
- "Rest mode" facility with remote control device.
- Reference Norms: EN 61347-2-7.
- Lamps: LED lamps 230V / GU10.



Code	Voltage	Frequency	Power W	Battery V-Ah	Flux %	ta °C	tc °C	Weight	Charge Time
EKT.003	220-240V	50...60Hz	3-6.5W	7.2V-1.6Ah	80/100%	0 +60	80	170gr	24h

### Technical Data:

- Length battery cable: 280mm.
- Length LED cable: 350mm.
- Led mounting hole: 8.8mm.
- Supply current: 20mA max.
- Push-wire connections max. size: 1.5mm<sup>2</sup>
- Max distance between driver and lamp: 2 meters.

### Battery:

- **Rechargeable high temperature Ni-Cd Saft batteries.**  
These cells accept a permanent charge for a minimum of 4 years in high-temperature environments (up to +50°C) such as security lighting equipment.
- Constant current during charge.
- Zero maintenance.
- Long cycle life (over 500 charge discharge cycles).
- Long term storage (up to 4 months in normal conditions: temperature range from +5°C to +25°C in a 65% ±5% relative humidity atmosphere).

