

GRAVITO XL 13

Exterior Inground, Surface, Wall, Bollard 

- Inground spot with honeycomb accessory
- Front plate: Stainless steel 316L
- Housing: Die-cast powder coated aluminum
- Mounting base: ABS 016
- Glass: Tempered glass, T=8mm
- Cable gland: IP-68 PG-9 PA66
- Power cable: H07RN-F 2x1.0mm² L=0.5m
- IK Rate: 07
- Ingress Protection: IP67
- PWM Dimmable
- Number of LEDs: 6
- Power Consumption: 12 Watt
- Maximum load: 2000kgs




LIGHTSOURCE BY
OSRAM

IP67


Model	CCT	Luminaire Lumen	Type	CRI	Beam Angle	Voltage	Accessories
GRAVITO XL ROUND 13.5W <i>(GRAVITO XL RD13)</i>	3000K (300)	783lm	Fixed (FX)	>80 (80)	9° (09)	24VDC PWM Dimmable (24)	COVER Standard (0/1) Honeycomb (1/1) ↓ (XX) ↑ EXTRAS No Extras (0/0)
	4000K (400)	870lm			15° (15)		
					20° (20)		
					30° (30)		
					45° (45)		
GRAVITO XL SQUARE 13.5W <i>(GRAVITO XL SQ13)</i>							

Ordering Code Example: GRAVITO XL RD13-300-FX-80-45-24-10

GRAVITO XL ROUND 13.5W



GRAVITO XL SQUARE 13.5W



ACC.232
Recessed Housing Box



ACC.279
Honeycomb supplied as extra