



Exterior Inground, Surface, Wall, Bollard

GRETTO TR WASH

- Gretto Wash is an outdoor luminaire available in trimless round version.
- Body material: aluminium
- Trimless box: Aluminium dark grey colour or Stainless Steel 316 (ordered as extra).
- Safety glass: 6mm
- Power cable HO5RN-F 2x0.75mm² L= 1m
- Cable outer diameter: 6.5mm
- Cable gland: IP67
- Optics available: lenses
- Static load resistance: 2000 kgs
- UGR<19 (Assymetric 27°x42°)
- L90/B10 50000h
- Ingress Protection: IP67
- IK Rate: IK07



CREE
LEDs

IP67

Model	LED Power	CCT	CR180 LED Source	CR190 LED Source	Beam Angle	Type	Dimming Option*	Extras
			80 (80)	90 (90)				
GRETTO Trimless WASH (GRETTO TR W)	4.1W (4)	2700K (27C) 3000K (30C) 4000K (40C) 5000K (50C)	440lm 440lm 475lm 410lm	355lm 380lm 410lm 440lm	Assymetric (AS) 27°x42°	Fixed (FX)	Without Driver (00) 24VDC PWM Dimmable (24DM) 48VDC PWM Dimmable (48DM)	No Extras (0) Emergency Kit (1)

* With external IP68 casing box Dali, Phase cut, 1-10V dimming also possible.

Ordering Code Example: GRETTO TR W4-30C-90-AS-RD-FX-00-0

