

- Gretto is an outdoor luminaire available in trimless round version.
- Body material: aluminium
- Trimless box: Aluminium dark grey colour or Stainless Steel 316 (ordered as extra).
- The luminaire can be customized with the use of softening lens, line spread lens and honeycomb supplied as extra.
- Safety glass: 6mm
- Power cable HO5RN-F 2x0.75mm<sup>2</sup> L= 1 m
- Cable outer diameter: 6.5mm
- Cable gland: IP67
- Optics available: lenses
- Static load resistance: 2000 kgs
- UGR<19 (6°, 15°, 30°, 46°)
- L90/B10 50000h
- Ingress Protection: IP67
- IK Rate: IK07



Model	LED Power	CCT	CRI80 LED Source	CRI90 LED Source	Beam Angle	Type	Dimming Option	Accessories
			80 (80)	90 (90)				
<b>GRETTO Trimless</b> (GRETTO TR)	<b>6.5W</b> (7)	2700K (27C)	713lm	570lm	15° (15)	Fixed (FX)	Without Driver (00)	<b>COVER</b> Standard (0X) Honeycomb (1X) Softening lens (2X) Line spread lens (3X) ↓ (XX) <b>EXTRAS</b> No Extras (10) Emergency Kit (11)
		3000K (30C)	713lm	615lm	30° (30)		24VDC PWM Dimmable (24DM)	
		4000K (40C)	765lm	660lm	46° (46)		48VDC PWM Dimmable (48DM)	
		5000K (50C)	765lm	713lm				
		6500K (65C)	765lm	-				
	<b>4.1W</b> (4)	2700K (27C)	440lm	355lm	6° (06)		Without Driver (00)	
		3000K (30C)	440lm	380lm			24VDC PWM Dimmable (24DM)	
		4000K (40C)	475lm	410lm			48VDC PWM Dimmable (48DM)	
		5000K (50C)	410lm	440lm				

\* With external IP68 casing box Dali, Phase cut, 1-10V dimming also possible.

Ordering Code Example: GRETTO TR7-30C-90-46-FX-00-10

