


- LEROS wall luminaire available with single or double light emission.
- Housing material: Die-cast powder coated aluminum
- Glass : PC T=6mm
- Power cable : HD5RN-F 3x1.0mm² L= 0.3m
- IK Rate: 06
- Outdoor installation: IP65
- Luminaire colour: Mat Grey

Monochromatic:


24VDC PWM Dimmable
230VAC Non-Dimmable



Leros 1Way



Leros 2Way



Model	Type	CCT	CRI80*, CRI90 LED Source		Voltage	Beam Angle**	Colour
			80 (80)	90 (90)			
LEROS (LEROS)	6W Leros 1Way (1x6W) (06)	2700K (27C)	810lm	670lm	24VDC PWM Dimmable (24)	18° (18)	Mat Grey (MG)
		3000K (30C)	860lm	700lm		25° (25)	
		4000K (40C)	880lm	740lm		42° (42)	
		5000K (50C)	900lm	770lm			
		5700K (57C)	860lm	-			
		6500K (65C)	870lm	-			
	12W Leros 2Way (2x6W) (12)	2700K (27C)	860lm	710lm	230VAC Non-Dimmable (230ND)		
		3000K (30C)	910lm	740lm			
		4000K (40C)	940lm	780lm			
		5000K (50C)	950lm	820lm			
		5700K (57C)	910lm	-			
		6500K (65C)	920lm	-			

* Nichia LEDs only in 3000K, CRI80 & Non-Dimmable.
** Also available with asymmetric up/down lenses upon request.

Ordering Code Example: LEROS 06-30C-90-24-42-MG

