

## METAL HALIDE LIGHT ENGINE

- Standard DMX512 signal control or Master/Slave control.
- Four DMX channels, 44 preset programs.
- Digital display.
- Dimmer / STROBE.
- Audio control.
- Twinkle effect.
- UV protected.
- Over-heat protection.
- Ch1: Color, CH2: Speed, CH3: Twinkle, CH4: Dimmer.

Code	Voltage	Lamp	Life of lamp	Max Aperture(mm)	Size(mm)	Weight(kg)
FOE.001 /150DMX	230VAC	CDM-T 150W	6000H	Φ30	L340×W320×H150	11,0



## HALOGEN LIGHT ENGINE

- Standard DMX512 signal control or Master/Slave control.
- Two DMX channels, 44 preset programs.
- Digital display.
- 8Colours
- Audio control.
- UV protected.
- Over-heat protection.
- Ch1: Color, CH2: Speed

Code	Voltage	Lamp	Life of lamp	Max Aperture(mm)	Size(mm)	Weight(kg)
FOE.003 /100DMX	230VAC	12V 50/75/100W Halogen	3000H	Φ22	L246×W205×H125	4,0



## IP43 LIGHT ENGINE

- Standard DMX512 signal control or Master/Slave control.
- Two DMX channels, 44 preset programs.
- Digital display.
- 8Colours
- IP rating: IP43
- Stainless steel enclosure.
- UV protected.
- Over-heat protection.
- CH1: Color, CH2: Speed

Code	Voltage	Lamp	Life of lamp	Max Aperture(mm)	Size(mm)	Weight(kg)
FOE.004 /150DMX/IP43	230VAC	CDM-T 150W	6000H	Φ30	L335×W328×H190	10,7



## DMX LED 80W IP43 LIGHT ENGINE

- Standard aperture: (Φ28mm / Φ30mm)
- IP Rating: IP43

Code	Total Power Consumption	Control Protocol	Colour	Light Source	Luminus Flux	Life of LED	Standard Aperture	IP
FOE.011	90W	DMX or by Remote Control	6 colours	80W CREE LED	6100lm (6000K)	50000H	Φ28mm Φ30mm	IP43

Accessories supplied with the engine

