


LOOP TR (Trimless)



- LOOP is a complete series of square with rounded corners luminaires available for surface, pendant, recessed and trimless application.
- The trimless version offers an elegant aesthetically solution for small and large scale projects.
- It consists of two models: High Power and High Efficiency.
- It is offered with a Low Glare (UGR<21.8*) as an option in the High Power model.
- It is offered with a Low UGR (UGR<18.6*) as an option in the High Efficiency model.
- Luminaire material: Aluminium.
- Cover material: PMMA
- Powder Coated: White (RAL9003)
- Custom luminaire colours also available on request.
- Low tolerances for colour temperature (MacAdam 3).
- Lumen maintenance L80/B10 50.000h
- Emergency Function capability. (3 hours, with build-in rechargeable battery).
- Indoor Use: IP40





LED source efficacy up to 197lm/W (4000K)
Luminaire efficacy up to 132lm/W (4000K)

Available upon request:

- ✓ Custom luminaire colours
- ✓ Emergency version

*Glare Evaluation: X=4H / Y=8H, S=0,25H, Reflection factors: 70/50/20








Model	Luminaire Colour	CCT	Watt / Diameter	CRI* LED Source	CRI* LED Source	Type	Voltage	Dimming Option	Extras	
LOOP Trimless High Power <i>(LOOP TR HP)</i>	White <i>(WH)</i>	3000K <i>(30)</i>	HIGH POWER		≥ 80 <i>(80)</i>	≥ 80 <i>(80)</i>	Opal <i>(OP)</i> Low Glare <i>(LG)**</i>	230VAC <i>(230)</i>	Non Dimmable <i>(ND)</i> Analogue (1-10V) <i>(A1)</i> DALI <i>(DL)</i> Wireless <i>(WL)</i>	Fuction Standard <i>(0)</i> Emergency <i>(1)</i>
			17.6W / 30x30cm <i>(18W3030)</i>	2660lm	2780lm					
			39.5W / 45x45cm <i>(40W4545)</i>	5860lm	6160lm					
			75W / 59x59cm <i>(75W5959)</i>	10720lm	11270lm					
			153.5W / 86x86cm <i>(154W8686)</i>	22150lm	23290lm					
			272.8W / 113x113cm <i>(273W113113)</i>	39380lm	41400lm					
			426.3W / 140x140cm <i>(426W140140)</i>	61540lm	64700lm					
LOOP Trimless High Efficiency <i>(LOOP TR HE)</i>	White <i>(WH)</i>	3000K <i>(30)</i>	HIGH EFFICIENCY		≥ 80 <i>(80)</i>	≥ 80 <i>(80)</i>	Opal <i>(OP)</i> Low UGR <i>(LU)**</i>	230VAC <i>(230)</i>	Non Dimmable <i>(ND)</i> Analogue (1-10V) <i>(A1)</i> DALI <i>(DL)</i> Wireless <i>(WL)</i>	Fuction Standard <i>(0)</i> Emergency <i>(1)</i>
			6.6W / 30x30cm <i>(07W3030)</i>	1130lm	1180lm					
			13.4W / 45x45cm <i>(13W4545)</i>	2250lm	2370lm					
			25.9W / 59x59cm <i>(26W5959)</i>	4200lm	4410lm					
			58.3W / 86x86cm <i>(58W8686)</i>	9450lm	9930lm					
			103.7W / 113x113cm <i>(104W113113)</i>	16790lm	17650lm					
			162W / 140x140cm <i>(162W140140)</i>	26230lm	27580lm					

* Available in CRI90 upon request.

** Low Glare (UGR<21.8), Low UGR (UGR<18.6)

Ordering Code Example: LOOP TR HP-WH-30-154W8686-80-LG-230-ND-0







LOOP Trimless

HIGH POWER	18W	40W	75W	154W	273W	426W
HIGH EFFICIENCY	7W	13W	26W	58W	104W	162W
Weight	1.55Kgs	3.46Kgs	6.24Kgs	11.70Kgs	18.80Kgs	28Kgs

HIGH POWER



HIGH EFFICIENCY

