LUMINET



Aluminium Profile

- LUMINET aluminium profile ideal for linear LED lighting applications. •
- Variety of accessories. .
- . Special design and construction to meet the most demanding lighting designs.
- Variety of beam angles.
- •
- .
- Variery or bearn angles. Multiple mounting options. Ideal for wall washing. Up to 12mm LED strip width (up to 10mm, at 70°). Available also in black, white or different RAL colours upon request. .











CEILING SUSPENSION Installation



SURFACE ADJUSTABLE installation



WALL BRACKET installation



SURFACE ADJUSTABLE installation





Image	Code	Description	Length	Design-Detail
	PRF.116	LUMINET alum.prof. / Anodized	2m	
				- \\
	PRF.117	SLIDING BASE alum.prof. / Anodized	2m	E
	COV.033	PMIMA LENS COVER Note 1: At 70° only 10mm LED strip width Note 2: Ideal for monochromatic LED strip	2m	
	COV.018 COV.017 COV.007	POLYCARBONATE CLEAR COVER POLYCARBONATE OPAL COVER PMIMA FROSTED COVER	2m 2m 2m	
	COV.023 COV.024 COV.025 COV.026 COV.038	POLYCARBONATE MILKY COVER POLYCARBONATE MILKY SATIN COVER POLYCARBONATE RULED COVER POLYCARBONATE CLEAR COVER POLYCARBONATE BLACK SATIN COVER	2m 2m 2m 2m 2m	90° ₩ 13mm
	CAP.115 CAP.116	FRONT CAP (aluminium) for LUMINET with END CAP (aluminium) for LUMINET with C		336mm
	CAP.117 CAP.118	FRONT CAP (aluminium) for LUMINET with END CAP (aluminium) for LUMINET with C		
	CAP.119 CAP.120	FRONT CAP (aluminium) for LUMINET with END CAP (aluminium) for LUMINET with C		
9.1.9.1	ACC.280	HINGE for SURFACE ADJUSTABLE installat (adjustable without tools)	ion (pair)	1 pair/2m
	ACC.281 ACC.282	WALL BRACKET 10cm (pair) WALL BRACKET 5cm (pair)		50mm 1pair/2m
L'. · ·	ACC.283	EXTENSION LINE for LUMINET		
	ACC.106 ACC.107	CEILING SUSPENSION INSTALLATION 150c CEILING SUSPENSION INSTALLATION 300c		ل کوری (m
151	PRH.001	HOLDER		20mm 16.5mm 20cs/m