






- Merlyn IP44 is a fixed downlight available with LED or with GU10 lamp holder for LED lamps.
- High antiglare rate due to its depth.
- Material : aluminium die cast.
- Variety of colour combinations.
- Variety of accessories: honeycomb/spread lens/soft lens/ line spread lens.
- 3 SDCM
- L90/B10 50000h
- Ingress Protection: IP44 (face only)



Model	LED Power	CCT*	LED Source	Type	CRI	Beam Angle	Colour**	Dimming Option	Accessories
<b>MERLYN IP44 Round</b> (MERLYN 44R)	<b>6.1W</b> (06)	2700K (27B)	812lm 677lm	Adjustable (AD)	80 (80) 90 (90)	16° (16) 25° (25) 36° (36) 50° (50)	White-White (WW) White-Black (WB) White-Gold (WG) Black-Black (BB) Black-Gold (BG)	Without Driver (00)	<b>COVER</b> Standard (0;) Honeycomb (1;) Line spread (2;) Softening lens (3;) Spread Lens (4;) (XX) <b>EXTRAS</b> No Extras (0) Emergency (1)
		3000K (30B)	845lm 705lm					Non Dimmable (ND)	
		4000K (40B)	879lm 733lm	Analogue (1-10V) (A1) DMX (DX) DALI (DL) Push Button (PB) Phase Cut (PC) Wireless *** (WL)					
<b>MERLYN IP44 Square</b> (MERLYN 44S)	<b>10.3W</b> (10)	2700K (27B)	1379lm 1138lm	Fixed (FX)	95 (95)			Analogue (1-10V) (A1) DALI (DL) Phase Cut (PC) Wireless** (WL)	
		3000K (30B)	1435lm 1180lm						
		4000K (40B)	1479lm 1265lm						
	<b>6.1W</b> (WD6)	Warm Dimmable 1800K--3000K (1890B)	CR195 518lm						

\* Models with CCTs of 3500K, 5000K & 6500K are available upon request.

\*\* Other RAL colours available upon request

\*\*\* The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example: MERLYN 44R-10-30B-FX-90-50-WW-ND-00

Model	Shape	Trim Colour	Type	Lamp Holder
<b>MERLYN IP44 Retrofit</b> (MERLYN 44 RE)	Round (RD)	White-White (WW) White-Black (WB) White-Gold (WG) Black-Black (BB) Black-Gold (BG)	Adjustable (AD) Fixed (FX)	GU10 (G1)



Ordering Code Example: MERLYN 44 RE-RD-BG-FX-G1

