

- Merlyn series consists of adjustable downlights in round or square form.
- Available in 18 / 25 / 32 Watt.
- Available with honeycomb, line spread and softening lens as extra.
- 3 SDCM
- L90/B10 50000h
- UGR<10



Model	LED Power*	CCT	LED Source	Type	CRI	Beam Angle	Colour	Dimming Option	Accessories
CRI95									
MERLYN XL Round <i>(MERLYN XLR)</i>	18W (18)	2700K (27L)	2000lm	Adjustable (AD)	95 (95)	24° (24)	White (WH)	Without Driver (00) Non-Dimmable (ND) Analogue (1-10V) (A1) DMX (DX) DALI (DL) Wireless** (WL)	COVER Standard (0:) Honeycomb (1:) Line spread lens (2:) Softening lens (3:) (XX)
		3000K (30L)	2115lm			38° (38)	Black (BL)		
		3500K (35L)	2177lm						
		4000K (40L)	2250lm						
		5000K (50L)	2313lm						
MERLYN XL Square <i>(MERLYN XLS)</i>	25W (25)	2700K (27L)	2613lm						EXTRAS No Extras (X0) Emergency Kit (X1)
		3000K (30L)	2763lm						
		3500K (35L)	2845lm						
		4000K (40L)	2940lm						
		5000K (50L)	3022lm						
32W (32)		CRI80 CRI90			80 (80) 90 (90)				
		2700K (27B)	4485lm			3701lm			
		3000K (30B)	4766lm			3868lm			
		3500K (35B)	4877lm			4009lm			
		4000K (40B)	4906lm			4092lm			
5000K (50B)	4962lm	4289lm							

*Lightsource by LUMINUS for 18W & 25W, and by BRIDGELUX for 32W
 ** The wireless dimming option includes driver and Bluetooth dimming accessory.

Ordering Code Example: MERLYN XLR25-40L-AD-95-38-WH-ND-00

