

MIDI U IP67

- MIDI U IP67 is a custom made linear luminaire available in standard or custom lengths.
- Supplied with single waterproof cable & IP68 connector as standard.
- Possibility for in-out cables & connectors upon request as extra.
- L90/B10 >50.000h, 3 Step MacAdam.
- Ingress Protection: IP67

Lighting management options:

On-Off/DALI/0..10V/1..10V/DMX512/PHASE CUT/IR/RF/PUSH BUTTON/Bluetooth

L90/B10 >50.000h
for monochromatic models

Available upon request:


- ✓ Custom dimensions
- ✓ Custom luminaire colours



Model*	Luminaire Colour	CCT	Type	Watt / Length	Voltage
MIDI U IP67 (MIDI U 67)	Anodized (AN)	2000K (20)	Clear (CL)	7W / 35cm (07W035)	24VDC (24)
	Marine Type (MT)	2500K (25)	Opal (OP)	12.2W / 60cm (12W060)	
		2700K (27)		17.5W / 85cm (17W085)	
		3000K (30)		21W / 102cm (21W102)	
		4000K (40)		24.5W / 119cm (24W119)	
		5700K (57)		31.5W / 152cm (31W152)	
				42W / 202cm (42W202)	

* IP67: Short term immersion protection

Ordering Code Example: MIDI U 67-AN-40-OP-31W152-24



Input cable with IP68 connectors (as standard)

PU (Polyurethane) material:

Tri- component polyurethane, transparent or translucent for homogeneous light dispersion.

Fully compliance with: REACH, RoHS and ELV European Directives.

EC – Directives 89/109 Contact with Food.

Resistance to: Outdoor – Chemicals – Short term water immersion – Hot water.

Thermal Shock – Heat – Abrasion

In accordance to: Florida test, Arizona test, Xenotest, QUV-A test, ACID Rain test ASTM G87, TABER test ASTM D1044, CROCKMETER test ASTM D6279

Marine Type features:

Powder Coating:

Ultra-durable powder coating that meets the requirements of GSB Master, Qualicoat Class2, EN12206 (formerly BS6496), EN13438 (formerly BS6497:1984) and AAMA 2604.

Exterior Durability:

Meets qualicoat class 2 requirements after 3 years Florida

Meets AAMA 2604-13 requirements after 5 years Florida

High Resistance to:

Weather, UV, Water and mould growth



WEATHER RESISTANT