

- NORDIA antiglare is an outdoor recessed downlight available in round form.
- Body material: aluminium.
- The luminaire can be customized with the use of softening lens, line spread lens and honeycomb supplied as extra.
- Power cable HO5RN-F 2x0.75mm<sup>2</sup> L= 1m
- Cable outer diameter: 6.5mm
- Cable gland: IP67
- Safety Glass: 6mm
- Optics available: lenses
- UGR<19 (6°, 15°, 30°, 46°)
- 3 SDCM
- L90/B10 50000h
- Ingress Protection: IP67
- IK Rate: IK07



**CREE** LEDs

IP67

Model	Power	CCT	CRI80, CRI90 LED Source		Beam Angle	Shape	Type	Colour*	Dimming Option**	Accessories
			80 (80)	90 (90)						
<b>NORDIA Antiglare</b> <i>(NORDIA AG)</i>	<b>4.1W</b> (4)	2700K (27C)	440lm	355lm	6° (06)	Round (RD)	Fixed (FX)	White (WH) Black (BL)	Without Driver (00)	<b>COVER</b> Standard (0/1) Honeycomb (1/1) Softening lens (2/1) Line spread lens (3/1) (XX)
		3000K (30C)	440lm	380lm					230VAC Non Dimmable (230ND)	
		4000K (40C)	475lm	410lm					24V/48DC Non Dimmable (2448ND)	
		5000K (50C)	410lm	440lm					24VDC PWM Dimmable (24DM)	
									48VDC PWM Dimmable (48DM)	
	<b>6.5W</b> (7)	2700K (27C)	713lm	570lm	15° (15)				Without Driver (00)	<b>EXTRAS</b> No Extras (1/0) Emergency Kit (1/1)
		3000K (30C)	713lm	615lm	30° (30)					
		4000K (40C)	765lm	660lm	46° (46)					
		5000K (50C)	765lm	713lm						
		6500K (65C)	765lm	-						
								230V Phase Cut (230PC)		



\* Other RAL finishes available on request.

\*\* With external IP68 casing box Dali, Phase cut, 1-10V dimming also possible.

Ordering Code Example: NORDIA AG 7-30C-90-46-RD-FX-BL-00-10

